



Oceanside Oak



■ Cadiz Oak EDCAD6O3MM



■ Barcelona Spruce EDBAR6S3MM



■ Granada Walnut EDGRA6W3MM



■ Tortosa Sisal EDTOR6S3MM



■ Madrid Maple EDMAD6M3MM



■ Valencia Teak EDVAL6T3MM



■ Caceres Acacia EDCAC6A3MM



■ Montecito Oak SMMON7O3MM



■ Redondo Oak SMRED7O3MM



■ Piedmont Oak SMPIE7O3MM



■ Riata Hickory SMRIA7H3MM



■ Oceanside Oak SMOCE7O3MM



■ Bridle Hickory SMBRI7H3MM



■ Terret Walnut SMTER7W3MM



■ Pelham Maple SMPEL7M3MM

## Features

- Length: 48"
- Width: ■ 6"  
■ 7.25"
- Thickness: 3mm  
20mil wear layer
- Finish: Surface Guardian Pro UV Coating
- Edge Detail: Microbevel
- FloorScore® Certified: Registration # SCS-FS-03695
- Warranty: Lifetime Residential Finish & Lifetime Residential Structure  
20 year Commercial Structural & 10 year Commercial Finish
- Maintenance: Clean with TrueClean Floor Cleaner.  
For full care and maintenance instructions visit  
[HallmarkFloors.com/Floor-Care-Maintenance](http://HallmarkFloors.com/Floor-Care-Maintenance)

## Benefits

- Fashion: Natural Low Sheen  
Embossed Wood Texture  
Fashionable Widths & Longer Lengths
- Performance: Waterproof  
Anti Bacterial & Fungal Control  
100% Renewable with Hallmark's ABC Recoat System  
PureCore Ultra- 100% Pure Virgin Vinyl
- Clean Air: Formaldehyde Free & Ortho Phthalate Free  
Safer Indoor Environment for Children  
100% FloorScore Certified



## Trim Options

- Multipurpose Reducer
- T-molding
- Flush Stair Nosing

## Installation



Glue Down

Double Glue with Eternity LVT underlayment system or equivalent.



## ASTM Testing

|  |                |               |
|--|----------------|---------------|
| Flexibility                                  | Pass           | ASTM F137     |
| Thickness Standard                           | Pass           | ASTM F386     |
| Resistance to Chemicals (5 min.)             | Pass           | ASTM F925 5   |
| Resistance to Chemicals (24 hr.)             | Pass           | ASTM F925     |
| Stain Resistance                             | Pass           | ASTM F925     |
| Heat Stability by Color Change               | Pass           | ASTM F1514    |
| Light Stability by Color Change              | Pass           | ASTM F1515    |
| Dimensional Stability after exposure to heat | Pass           | ASTM F2199    |
| Fire Resistance                              | Class C - Pass | ASTM E 648    |
| Coefficient of Friction                      | Pass           | ASTM D2047-04 |
| Static Load                                  | Pass           | ASTM F970-07  |
| Stain Resistance                             | Pass           | ASTM F925     |
| Short Term Indentation                       | Pass           | ASTM F1914-98 |
| Smoke Density                                | Pass           | ASTM E662-09  |
| Wear Resistance                              | High           | ASTM F510-93  |
| Formaldehyde Emission (air)                  | None Detected  | EN 7171-1     |

## ISO 14001 Certified Environmental Management System



Certified FloorScore: Independent 3rd Party IAQ verification system for low emitting flooring. Approved as CHPS 01350 compliant and recognized in LEED EQ Credit 4.3